

## Sizes for Dynamic Dome Skylights

Sizes	24" width			36" width			48" width			60" width			72" width		
	size code	outside curb	max clearance	size code	outside curb	max clearance	size code	outside curb	max clearance	size code	outside curb	max clearance	size code	outside curb	max clearance
36" length				<b>3636</b>	39" x 39"	40 ¼" x 40 ¼"									
48" length	<b>2448</b>	27" x 51"	28 ¼" x 52 ¼"				<b>4848</b>	51" x 51"	52 ¼" x 52 ¼"						
60" length				<b>3660</b>	39" x 63"	40 ¼" x 64 ¼"	<b>4860</b>	51" x 63"	52 ¼" x 64 ¼"	<b>6060</b>	63" x 63"	64 ¼" x 64 ¼"			
72" length				<b>3672</b>	39" x 75"	40 ¼" x 76 ¼"	<b>4872</b>	51" x 75"	52 ¼" x 76 ¼"	<b>6072</b>	63" x 75"	64 ¼" x 76 ¼"	<b>7272</b>	75" x 75"	76 ¼" x 76 ¼"
83" length							<b>4783</b>	50" x 86"	51 ¼" x 87 ¼"						
96" length	<b>2496</b>	27" x 99"	28 ¼" x 100 ¼"	<b>3696</b>	39" x 99"	40 ¼" x 100 ¼"	<b>4896</b>	51" x 99"	52 ¼" x 100 ¼"	<b>6096</b>	63" x 99"	64 ¼" x 100 ¼"			
120" length	<b>2412</b>	27" x 123"	28 ¼" x 124 ¼"	<b>3612</b>	39" x 123"	40 ¼" x 124 ¼"	<b>4812</b>	51" x 123"	52 ¼" x 124 ¼"	<b>6012</b>	63" x 123"	64 ¼" x 124 ¼"			


### Options

LuxGuard (Polycarbonate)  
**Stocked in ALL sizes for quick shipment**  
 15-Year Warranty - including hail breakage up to 2"


IMA Impact Modified Acrylic  
 Stocked in 4848/4896/6072 for quick shipment  
 5-Year Warranty

LuxGuard Plus (Polycarbonate)  
 HVHZ Zones  
 No stock  
 15-Year Warranty - including hail breakage up to 2"

## Curbs for Dynamic Dome



**Curb: CCA6**  
**Insulation:** Field Insulated – Single Wall  
**Material:** Galvanized Steel  
**Height Options:** 9", 12", 16", 18"



**Curb: CCA3**  
**Insulation:** Factory Insulated – Double Wall  
**Material:** Galvanized Steel  
**Height Options:** 9", 12", 16", 18"



**Curb: CCAM**  
**Insulation:** Factory Insulated – Double Wall  
**Material:** Aluminum  
**Height Options:** 9", 12", 16"



**Curb: CCAN**  
**Insulation:** Factory Insulated – Single Wall  
**Material:** Aluminum  
**Height Options:** 9", 12", 16"

## Fall Protection for Dynamic Dome



**Exterior safety screen**  
**CAE/STS**



**Interior safety screen**  
**CRGA ICD**



**Interior security bars**  
**CRGA BB/SB**

8" o.c. both directions (BB)  
 5" o.c. one direction (SB)

The safety of others is of the utmost importance to VELUX. In addition to selecting the correct skylight for the application, VELUX recommends that the customer consider protecting all skylight openings and skylights with one or more of the fall protection accessories. VELUX recommends that the building owner or manager restrict roof access only to personnel who have been sufficiently cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights. Building owner or manager should provide fall protection around the skylight in accordance with OSHA regulations.

