



UniQuad® Solar and Thermal Performance per NFRC Standards

Configuration				Performance Values		
Exterior Glazing (10mm)	Interior Glazing (10mm)	Additional Insert	Frame Finish	U-factor	Solar Heat Gain Coefficient (SHGC)	Visible Transmittance (VT)
Clear Matte	Clear Matte	-	Mill Finish	0.26	0.34	0.34
			Anodized or Painted	0.29		
		Nano 1-28 Insulation	Mill Finish	0.22	0.25	0.21
			Anodized or Painted	0.25		
		Nano 2-28 Insulation	Mill Finish	0.17	0.2	0.16
			Anodized or Painted	0.19		
		Super Nano Insulation	Mill Finish	0.17	0.18	0.11
			Anodized or Painted	0.19		
Clear Matte	White Matte	-	Mill Finish	0.26	0.32	0.19
			Anodized or Painted	0.29		
Clear Matte	Ice White Matte	-	Mill Finish	0.26	0.34	0.28
			Anodized or Painted	0.29		
White Matte	Clear Matte	-	Mill Finish	0.26	0.3	0.16
			Anodized or Painted	0.29		
White Matte	White Matte	-	Mill Finish	0.26	0.23	0.1
			Anodized or Painted	0.29		
White Matte	Ice White Matte	-	Mill Finish	0.26	0.27	0.13
			Anodized or Painted	0.29		
Ice White Matte	Clear Matte	-	Mill Finish	0.26	0.34	0.29
			Anodized or Painted	0.29		
Ice White Matte	White Matte	-	Mill Finish	0.26	0.29	0.16
			Anodized or Painted	0.29		
Ice White Matte	Ice White Matte	-	Mill Finish	0.26	0.33	0.24
			Anodized or Painted	0.29		

Test results are listed under CPI Daylighting in the NFRC Certified Products Directory - 4" UniQuad®

Kingspan Light + Air
 North America
 28662 N Ballard Drive
 Lake Forest, IL 60045
 t: +1 847 816 1060
 f: +1 847 816 0425
 info@kingspanlightandair.us
 www.kingspanlightandair.us

NFRC COE UQ4, Revision 1, 0522