

# Optimo®



Optimo® delivers a clean, smooth and aesthetically appealing modern solution. Incorporating superior airtightness as well as high R-value.

Kingspan's Optimo® gives you that, and more, available in either a non-embossed or embossed texture. Optimo's single component design can reduce on-site installation time by up to 50% compared to traditional site assembled systems. Optimo® is suitable for high volume, large scale, new and retrofit applications across the commercial and industrial sectors.



Insulation Core:	QuadCore® Technology or PIR
Profile:	Exterior: Flat / Interior: Shadowline or flat
Embossing:	Exterior: Stucco or non-embossed / Interior: Stucco or non-embossed
Gauge:	Exterior: 22 ga / Interior: 26, 24, 22 ga
Width:	24", 30", 36", 40"
Thickness:	2", 2.5", 3", 4", 5", 6"
Length:	Embossed: 8' - 32' / Non-embossed: 8' - 20'
Reveal option:	Vertical: 1/8", 1" or 2" / Horizontal: 1/8", 3/8", 1" or 2"
Orientation:	Vertical or horizontal
Post fabrication (optional):	Trimless ends, folded corners, transverse bends. (Manufacturing limitations apply. Please contact us for detailed information.)
R-value:	QuadCore® Technology: ≈ 8 per inch per ASTM C518 @ 75°F mean temperature / ≈ 9 per inch per ASTM C518 @ 35°F mean temperature PIR: ≈ 7.2 per inch per ASTM C518 @ 75°F mean temperature / ≈ 8.25 per inch per ASTM C518 @ 35°F mean temperature



